

Terms & Conditions- SCRAP DISPOSAL OF 16" DIA PIPE LENGTHS

- The amount of Earnest Money/ Bid Security for the above tender is 2% of the total quoted amount in the form of pay order in favor of HASCOL PETROLEUM LIMITED
- Bid of any bidder shall be cancelled if the bidder is found blacklisted by any organization at any stage during tendering process or execution of the Contract. The bid of any bidder shall be declared non-responsive if he is found involved in litigation with any government or semi-government department
- If any clarification is required, the query may be sent to procurement@hascol.com, at least 03 days prior to the date fixed for submission of bids. All replies to the queries or addendum etc. shall be considered part of the bidding documents and should be signed and submitted along with the Bid.
- In case of any unforeseen reasons, unrest or force majeure on the bid submission/opening date, the tender shall be opened on the next working day at the same place and time.
- The Bids shall remain valid for a minimum period of 90 days from the date fixed for submission of the Bids.
- Incomplete, conditional and Bids without appropriate earnest money shall not be considered.
- This tender is only invitation to offer and HASCOL PETROLEUM LIMITED does not bind itself to accept any Bid.

MTC is attached for reference.

Length of pipe (m)	Total (Kg)
123.36	9,594.46

Extracted 16" pipe details	
Pipe no.	Length (m)
1	11.14
2	11.96
3	11.9
4	11.7
5	11.95
6	12.05
7	16.15
8	11.56
9	12.7
10	12.25
Total	123.36



厦门兰地进出口有限公司
XIAMEN LANDEE INDUSTRIES CO., LTD.

MILL TEST CERTIFICATE

ADD: SUITE 2201 HUITENG METROPOLIS,
NO. 321 JIAHE ROAD, XIAMEN, CHINA.
TEL: (86)592-5204188 FAX: (86)592-5204189
web: www.landee.cn

MESSRS: HASCOL PETROLEUM LIMITED,
'THE FORUM' 1ST FLOOR, SUITE
NO.105-106, G-20, KHAYABAN-E-JAMI,
BLOCK-9, CLIFTON, KARACHI-PAKISTAN.

CERT NO.: LD-MTC1604158A
DATE: 31ST MAY 2016

L/C NUMBER:122SLCPUS087816 DATE OF ISSUANCE:160427 NAME OF ISSUING BANK:SUMMIT BANK LTD

Product name: CARBON STEEL PIPES

Standard: API 5L PSL1

Material:L245

Batch No.	Heat No.	Specification		PC	M	Chemical Composition (%)						physical properties					appearance	NDT		Hydrostatic (10s) Mpa	Eligible item number	
		Diameter	Thickness			C	Si	Mn	P	S	CE	base material		physical properties				UT	RT			
												Yield Strength	Ultimate	Elongation	face bend	back bend						ob Mpa
		mm	mm									Mpa	Mpa	δ(%)	180°	180°						
16G45	1605R0895	406.4	7.92	265	3153	0.11	0.1	0.92	0.019	0.010	/	354	461	44	pass	pass	498	pass	pass	pass	5.7	15
16G45	1605R0502	406.4	7.92	130	1547	0.10	0.1	0.92	0.018	0.008	/	374	471	40	pass	pass	506	pass	pass	pass	5.7	15
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

State:1.If pressure-bearing pipes and general pipes was using mixed, we only guarantee according to the general pipes.2.The damages during the handing and transportation was not in the scope of inspection.3.If there's any objections to our products, please put forward in written form within three months, over this period, the company will not be accepted.4.When you come to check the objection, please bring the company product certificate and contract.

Person in charge:Zheng Tongbin

Operated by: Yin Guihua

Consigner: Gao Ming

XIAMEN LANDEE INDUSTRIES CO.,LTD.
厦门兰地进出口有限公司

陈兰芳

Authorized Signature



厦门兰地进出口有限公司
 XIAMEN LANDEE INDUSTRIES CO., LTD.

MILL TEST CERTIFICATE

ADD: SUITE 2201 HUITENG METROPOLIS,
 NO. 321 JIAHE ROAD, XIAMEN, CHINA.
 TEL: (86)592-5204188 FAX: (86)592-5204189
 web: www.lanDee.cn

MESSRS: HASCOL PETROLEUM LIMITED,
 'THE FORUM' 1ST FLOOR, SUITE
 NO.105-106, G-20, KHAYABAN-E-JAMI,
 BLOCK-9, CLIFTON, KARACHI-PAKISTAN.

CERT NO.: LD-MTC1604158B
 DATE: 31ST MAY 2016

L/C NUMBER:122SLCPUS087816 DATE OF ISSUANCE:160427 NAME OF ISSUING BANK:SUMMIT BANK LTD

Product name: 3LPE COATING

Standard: DIN30670

Size(mm)	Quantity		Surface treatment level	Coating technical indicators					Coating quality inspection			
	Length (M)	PC		Peel strength(N/cm)		Cathodic disbondment (65°C,48h)/mm	Impact Strength/(J/mm)	Bend resistance (2.5°)	Surface(smooth, without dark bubbles, no pitting, no fold, no crack)	Electric spark leakage detection(KV)	Pipe coating thickness direction around four o'clock(mm)	Tensile strength and elongation at break(%)
				20°C±5°C	50°C±5°C							
406.4*7.92	11.9	395	Sa2.5	pass	pass	pass	pass	pass	pass	25	2.2	600

person in charge:Liu Shuhua

Inspector:Zhou Guanglan

XIAMEN LANDEE INDUSTRIES CO.,LTD.
 厦门兰地进出口有限公司

陈兰芳

Authorized Signature